

5. (Canceled) Polyurethane spring mattress (1) according to the first claim, characterised in that each spring (5) acts as a perfectly elastic part that, after being deformed under the action of a force, recovers its original shape and position in a natural way once the action of said force has ceased.

6. (Canceled) Polyurethane spring mattress (1) according to the first claim, characterised in that it is provided with a visco-elastic layer of polyurethane (3) and knit padding (2).

7.- (New) Polyurethane foam spring mattress according to Claim 1, wherein said nucleus having said plurality of springs is made up from said block of polyurethane foam by means of an automatic programmable machine that cuts interiorly along a larger side of said block a first pair of mutually opposite zigzagged walls of said springs and, turning said block 90°, said programmable machine cuts interiorly along a smaller side of said block a second pair of mutually opposite zigzagged walls of said springs, and exceeding material is removed from inside said block, whereby said plurality of springs is formed internally to said block and the number of turns of said springs depends on the position of each spring along said larger and smaller sides.

## **REMARKS**

### ***Information Disclosure Statement***

As requested by the Examiner, Applicant is now submitting an IDS listing the prior art together with copies of the patents listed in the International Search Report other than U.S. Patents:

- EP0367607 A1 (Span America, Medical Syst);
- DE 19919502 C1 (Huelsta Werke Huels);
- ES 1028212 U (José Manuel Gregorio Casamian et al); and
- The fourth patent, U0186551 U (Enrique Ayuso Canovas, classified A), cannot be retrieved

### ***Claim rejections***

Claims 2-6 were rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as his invention.

Claims 2, 3, 5 and 6 are canceled.

Claim 4 is amended. Care has been taken to correct errors of the original claim (narrative in form, with indefinite and functional or operational language, not in one sentence form only, dependence on the first claim)

Claims 1 and 5 are rejected 35 U.S.C. 102(b) as being clearly anticipated by Luke.

Claim 5 is canceled.

Claim 1 is amended.

Luke discloses a mattress overlay (col. 3, lin. 54-55), that is not a mattress, having a thickness of 2 inches (2/40-41). The mattress of the application has a thickness of 180 cm. The overlay features external pyramidal springs with flat surfaces while the mattress of the application features internal or external springs, with zigzagged walls that simulate a helical or pyramidal spring. Also, the overlay production involves a substantial waste of foam, whereas the mattress of the second embodiment is made up in only one operation with minimum waste of raw material. For these reasons the applicant believes that Luke does not anticipate the mattress of the application.

Claim 6 was rejected under 35 U.S.C. 103 (a) as being unpatentable over Luke in view of Landvik et al, teaching the use of the addition of a viscoelastic foam layer to a mattress.

Claim 6 is canceled and the viscoelastic foam layer is included as one of the components of the mattress in amended claim 1, but this feature does not constitute an innovation in the invention and therefore is not specifically claimed.

Claims 2-4 were rejected under 35 U.S.C. 103 (a) as being unpatentable over Luke in view of Raburn et al.

Claims 2-3 are canceled.

Raburn et al disclose a support pad with uniform patterned surface featuring transversal ribs and complementary troughs. All ribs (springs) are equal and symmetric and fill the entire width of the pad. Also, the ribs are external to the pad. However, the application discloses a mattress having internal or external springs, with zigzagged walls mutually displaced each respect to the opposite wall, thus imitating a real helical or conical

wire spring. Additionally, in the case of "helical" springs, they may have different number of turns according to the corresponding position along the longitudinal and transversal dimensions of the mattress depending on the stress the area must support. Applicant respectfully traverses the opinion of the Examiner and states that the features of the springs are not obvious in comparison to Luke and Raburn. The same conclusions must be reached in respect of the amended Claims 1 and 4 and new Claim 7 now submitted.

Poppe, which is cited as relevant art, discloses an elastic springy element, which consists of a tubular body made of synthetic foam material, where the wall of the body displays a number of hollows in staggered symmetry. These springs are completely different from those of the application along with the fact that are produced one by one to be glued between two support layers, whereas the mattress of the application features springs with turns that form a single piece with the support and are shaped by means of two cutting operations on a block of foam.

Torres, which is cited as relevant art, discloses a spring mattress based on foam where the springs are equal and external or with another slab of foam glued on top (Figs. 3, 4 and para. 0009, lin. 8-10 and 14-16). Additionally are obtained by means of two operations of cutting and pouring (para. 0009, lin. 2-3). The mattress of the application features internal springs obtained by means of a single operation of cutting.

According to the above mentioned arguments, applicant has worded Claim 1 (amended), Claim 4 (amended) and Claim 7 (new) which contain what the applicant believes is the essence of the invention.

Amended claim 1 details the mattress components focusing on the fact that each spring has pairs of opposite zigzagged walls and the zigzagged walls are mutually displaced thus imitating a real wire spring.

Amended claim 4 details an embodiment of the invention having external springs with truncated pyramidal configuration, where, by means of a single cutting operation, two equal and complementary mattresses are obtained with a minimum waste of foam.

New claim 7 details another embodiment of the invention having internal springs with variable configuration according to their position in the mattress and the operations performed to realise the mattress.

Amended Claims 1 and 4, as well as new Claim 7 are now referred to in order to identify the antecedent basis of their contents. In that follows, reference is made (in parentheses) to the applicable page/line of the original PCT specification where the antecedent basis for any amendment or addition can be found.

1. (Amended) Polyurethane foam spring mattress (1), [characterised in that the main body is] comprising a nucleus made from a single block of said material (page/line 2/17-18, 3/1-2, 5/32)

[and is provided with] having a plurality of springs (5) [of variable resistance to compression] with pairs of mutually opposite zigzagged walls being said zigzag of a first wall of each pair displaced with respect to said zigzag of a second wall of the same pair in such a way that each protruding part of said first wall zigzag coincides substantially with an inward part of said second wall of the same pair; (page/line 6/16-20);

a visco-elastic layer of flexible polyurethane foam 4 cm thick adhered on top of said nucleus

(page/line 3/3-4, 7/10-11);

and a three dimensional knit padding.

(page/line 3/6, 7/11)

4. (Amended) Polyurethane foam spring mattress (1) according to [the first] claim 1, [characterised in that] wherein the springs (5) of said mattress have the shape of the trunk of a pyramid (9) with pairs of mutually opposite zigzagged walls (page/line 6/16-20),

[and are provided with spirals (5.1)] and wherein a pair of said nuclei having said plurality of springs are shaped [by cutting a parallelepiped rectangular] in one process

(page/line 6/24-32)

from said block of polyurethane foam by means of a [specific] programmable machine with [in two steps: a first step for shaping by means of a cutting] a blade [manoeuvred by said machine, which covers] covering the entire length or width of [the] said polyurethane block

(page/line 6/11-12),

said blade cutting firstly a first pair of mutually [two first] opposite [faces of each] zigzagged walls of said springs (5) [and partially, two platforms (6) into which

all of the springs (5) of each mattress (1) are integrated, and a second step for shaping by means of the same cutting blade manoeuvred by said machine, which covers the entire length or width of the polyurethane block, a second pair of opposite faces adjacent to the first two faces and completely the two platforms (6) in which all of the springs (5) of each mattress are integrated, after turning said block 90° around a vertical axis, producing less than 1% of the material of the block as waste product since two essentially equal and complementary pieces are obtained.] along a longitudinal dimension of said block and secondly along a transversal dimension of said block, whereby both nuclei of said pair of nuclei having said plurality of truncated pyramidal springs are complementary and substantially equal.

(page/line 6/24-35)

and said pair of nuclei use substantially the entire block of polyurethane foam.

(page/line 6/35-7/7).

7.- (New) Polyurethane foam spring mattress according to Claim 1, wherein said nucleus having said plurality of springs is made up from said block of polyurethane foam by means of an automatic programmable machine that cuts interiorly along a larger side of said block a first pair of mutually opposite zigzagged walls of said springs and, turning said block 90°, said programmable machine cuts interiorly along a smaller side of said block a second pair of mutually opposite zigzagged walls of said springs, and exceeding material is removed from inside said block.

(page/line 2/17-22, 5/32-6/6, and Figs.),

whereby said plurality of springs is formed internally to said block and the number of turns of said springs depends on the position of each spring along said larger and smaller sides.

(page/line 2/17-33)

In view of the above, reconsideration and allowance of the pending claims are respectfully solicited.

Respectfully submitted

Ricardo Alonso Cucurull

A large, stylized handwritten signature in black ink, consisting of a series of loops and a long horizontal stroke, is written over the printed name.

**Amended Specification, including Amended Claims (Red Line Version)**

## FOAM SPRING MATTRESS

### OBJECT OF THE INVENTION

This invention relates to a new type of mattress, completely made of foam, synthetic rubber, etc., and which is provided with a number of springs made up of the same material as that of the mattress itself.

### BACKGROUND OF THE INVENTION

There are currently a great number of types of mattresses on the market that ensure giving people's bodies beneficial rest, and which also must fulfil the function of giving people proper support, being neither too soft nor too hard. The main varieties are the following:

- Wool mattress: currently they are produced very infrequently, because wool has been replaced by new materials. This type of mattress has as a drawback that with use, the wool becomes lumpy and that every two or three years it has to be re-carded so as to restore its consistency. In addition, mattress makers are very scarce nowadays.
- Spring mattress: it is made of steel springs that can be bi-conical (the upper and lower [spirals] turns are bigger than the central ones), or [cylindrical] helical (the [spirals] turns have all got the same diameter), and they are often individually [insulated] isolated in order to prevent noise. On either side of the springs, the filling-holder is lined with a layer of horsehair, sisal or felt; a cotton, wool or synthetic fibre filling, which in turn are also lined; and finally, the whole assembly is closed into the outer cover. These mattresses are solid and comfortable.

"Multi-elastic" mattresses differ from those of traditional springs in that they have a kind of thick net of metallic thread.
- Synthetic latex mattress: a chemical reconstruction of natural latex. These mattresses have a flat surface, and another one full of cells that



facilitate air circulation. They are very hygienic, but sensitive to light when they are exposed to it without their covers.

- 5       • Polyester mattress: the density of polyester used for producing mattresses must not be less than  $25 \text{ kg/m}^3$ . The softness of the foam depends on this density. Since the regulations are not always respected, this type of material has acquired an undeservedly bad reputation. Before buying one of these mattresses, the consumer should insist that the density of the foam rubber should be specified. It  
10       should also have a thickness of, at least, 10 cm to be of good quality.

With the objective of solving the described problems, a new type of mattress has been developed, which is described below.

## 15       **DESCRIPTION OF THE INVENTION**

This invention consists of a new type of mattress that is made from a block of flexible polyurethane foam of  $40 \text{ Kg/m}^3$  or of any other density, and later with an automatic programmable machine, the interior of said block is cut first on its larger side  
20       and later turning the block  $90^\circ$ , or turning to another angle in which case the springs would remain in an oblique arrangement, by the smaller side or vice-versa, thus forming a certain quantity of springs that depends on the size of each type of mattress. It can also be produced by injection, or by any other method.

25       The number of [spirals] turns that each spring has depends on the position of each one within the mattress with the objective of varying its flexibility and that the mattress should adjust perfectly to the shape of every individual person in [the] a first shape of the mattress. However, in a second shape of the mattress designed to use each block of polyurethane foam [to the maximum] entirely, the springs have the same  
30       number of [spirals] turns throughout the entire surface of the mattress and the pressure created by each spring will depend on its deformation, being greater the more it is compressed, adjusting itself to the pressure points of the person who will be using it, reducing the pressure where other mattresses do not have such flexibility.

The nucleus of this type of spring mattress is made of a single piece and with a single material, or starting with a block that can be made by gluing pieces of different materials and densities. The product is completed on its upper face with a visco-elastic layer of flexible polyurethane of 50 Kg/m<sup>3</sup> and 4 cm thick; or else the nucleus  
 5 can be finished with a flat shape using the same material as the block, and finally it can optionally include a three-dimensional knit padding.

The densities of the aforementioned materials are average values, these mattresses being amenable to the use of other, similar materials and with different  
 10 densities depending on the desired reduction of pressure in the support areas.

This mattress offers a number of advantages with respect to traditional mattresses, which are the following:

15 -They only sink down in the areas where they receive pressure. This property is maximally useful when the mattress is used by a couple with relatively different weights, thus preventing the person that weighs less from sliding towards the person that weighs more, maintaining the pressure in a proportional manner while avoiding deforming the mattress.

20

-It facilitates changing position.

-It facilitates adequate blood circulation, decreasing the pressure placed on the skin and greatly reducing the appearance of bedsores, and likewise decreasing the  
 25 healing period of patients that already suffer from bedsores.

-They relieve the pain of patients that suffer from bone fragility

-Comfortable and adaptable to the body.

30

-Greater durability than traditional spring mattresses.

-Free from toxic substances. It is totally innocuous upon body contact.

35

-Bactericide. Anti-allergenic. Fireproof. Recyclable.

This type of spring cut from a block of foam can be used not only for mattresses but also for any other kind of padded furniture, such as chairs, armchairs, seats, backrests and lower back support for vehicle seats, or for accessories such as pillows or cushions, whether they are conventional, wedge-shaped or cervical, neck supports, etc.

## DESCRIPTION OF THE DRAWINGS

In order to complete the description of the invention and with the objective of improving the understanding of its characteristics, a set of figures is attached in which in a purely illustrative and non-limiting manner, the following are represented:

Figure 1A is a view from the larger side of a two-place mattress (1) of polyurethane foam (4). The upper surface of the mattress (1) has a polyurethane visco-elastic layer (3) and padding (2). The springs (5) and the hollowed-out area (5.2) are shown, the outline of which is formed by the [spirals] turns (5.1) of each spring (5).

Figure 1B is a view of the smaller side of a two-place mattress (1) of polyurethane foam (4). The upper surface of the mattress (1) has a layer of visco-elastic polyurethane (3) and padding (2). The springs (5) and the hollowed-out area (5.2) are shown, the outline of which is formed by the [spirals] turns (5.1) of each spring (5).

Figure 2A is a view of the larger side of a one-place mattress (1) of polyurethane foam (4). The upper surface of the mattress (1) has a layer of visco-elastic polyurethane (3) and padding (2). The springs (5) and the hollowed-out area (5.2) are shown, whose outline is formed by the [spirals] turns (5.1) of each spring (5).

Figure 2B is a view of the smaller side of a one-place mattress (1) of polyurethane foam (4). The upper surface of the mattress (1) has a layer of visco-elastic polyurethane (3) and padding (2). The springs (5) and the hollowed-out area (5.2) are shown, whose outline is formed by the [spirals] turns (5.1) of each spring (5).

Figure 3A is a perspective view of a two-place mattress (1) of polyurethane foam (4). The upper surface of the mattress (1) has a layer of visco-elastic polyurethane (3) and padding (2). The distribution of the springs (5) is also visible on the larger side and on the smaller side of the mattress (1).

5

Figure 3B is the enlarged view of a spring (5) cut out of the interior area of a mattress (1) of polyurethane foam (4), in which the [spirals] turns (5.1) and the hollowed-out area (5.2) are detailed. The layer of visco-elastic polyurethane (3) and the padding (2) are also visible.

10

Figure 4 is the profile view of a mattress (1) of polyurethane foam (4) with the springs (5), the spirals (5.1), the hollowed-out area (5.2), the layer of visco-elastic polyurethane (3) and the padding (2). It is also shown how the mattress (1) adapts perfectly to the shape of the person (6) resting on it.

15

Figure 5 illustrates another, alternative form of mattress spring with lines that facilitate its use in mattresses of lesser thickness, such as cot mattresses. They are compressed as the aforementioned ones, and are three-dimensional, and are made with parallel and/or non-parallel cuts on two faces of the block as shown.

20

Figure 6 illustrates in a schematic manner an alternative form for the mattress of the invention where it can be seen how, within a parallelepiped block of polyurethane or other material, it can be made by cutting out two parts, each of them constituting the nucleus of a pyramid-trunk type spring mattress, the springs of each piece being complementary to the other piece with which it formed the block.

25

### **[PREFERRED EMBODIMENTS] DETAILED DESCRIPTION OF THE INVENTION**

Among the different types of spring mattresses that can be built based on this invention, the preferred embodiments are those described below.

30

In a first preferred embodiment (Figs. 1A-4), starting with a block of polyurethane foam (4) with a density of 40 Kg/m<sup>3</sup> or that which is in accordance with the use and the model and size of each mattress (1), the [spirals] turns (5.1) are cut

with an especially designed machine [expelling the excess] removing exceeding material from the hollowed-out areas (5.2) and shaping the springs (5).

In order for each spring (5) to be shaped, the machine must first carry out the  
5 [spiral] turn (5.1) cutting along the larger side of the mattress (1) and later along the smaller side. In this way, the four sides of each spring are perfectly cut and shaped.

In a second preferred embodiment, the starting point is a parallelepiped rectangular block of polyurethane or other material, in accordance with the length and  
10 width that the final mattress should have, with a density of 40 kg/m<sup>3</sup> or that which is appropriate in accordance with its use, and it is cut by way of a blade that covers all of the length or width of the block, manoeuvred by an arm and a programmable machine.

Fig. 5 illustrates an alternative form of mattress spring with lines that facilitate  
15 its use on mattresses of lesser thickness, such as cot mattresses.

In Figure 6, by way of the solid-line arrows, the course of the blade in relation to one of the lateral sides of the block is shown, though only partially. The blade attacks the block at the tip (7) and cuts the lateral walls of a pyramid trunk (9), the  
20 walls of which are not straight but rather zigzagged, with the particular feature that on the opposite wall, the zigzag is displaced with respect to the other wall so that the most salient part of one substantially coincides with the inward part of the other, thus imitating the structure of a traditional spring of elastic material. After cutting out as many lateral walls as have been programmed, the blade is removed from the block at  
25 the tip (8) and returns to starting position (10).

It should be noted that up to now the block has been cut into two equal, complementary pieces formed by a platform (6) from which the pyramid trunks (9) jut out, which up to now only have two faces formed, one fitted into the other.

30

The block is then turned 90° on a vertical axis and the same process is carried out, so that the pyramid trunks (9) that form the springs (5) are completely cut out with four lateral zigzagging walls and the two bodies or nuclei of the mattress (1) that are  
35 formed by this process are completely separated. It is noteworthy that in this

procedure, as well as forming two mattresses (1) at once, there is a minimal waste of polyurethane block mass or of other material, because both mattresses (1) are equal and complementary. For example, two mattresses (1) can be obtained from a 173 mm-thick block, made up of a 25 mm-thick platform (6) and with a total height of 148 mm, thus making use of 100% of the material. More specifically, two mattresses (1) of 180 x 900 x 1900 can be obtained from a block of 210 x 900 x 2000 mm; from which, as can be seen, 30 mm of thickness is lost due to the platforms (6), 100 mm in length due to a border (not shown) that is a result of the cutting process and is not usable, and no width at all is lost in the mattresses formed with respect to the width of the original block.

To finalise the production of the mattress (1), once the springs (5) have been cut, an upper layer of visco-elastic polyurethane (3) can optionally be ad[d]hered to said mattress (1), including knit padding (2).

15

Having sufficiently described the nature of this invention, as well as a practical application of the same, it only needs be added that modifications may be added in both its shape and its materials, as well as its production procedure, as long as these modifications do not substantially affect the characteristics claimed below.

**CLAIMS**

1 – Polyurethane foam spring mattress (1), characterised in that the main body is made from a single block of said material and is provided with a plurality of springs (5) of variable resistance to compression.

2 – Polyurethane spring mattress (1) according to the first claim characterised in that the springs (5) of said mattress are provided with spirals (5.1) that are shaped by cutting the aforementioned block with a specific machine and discarding the excess material.

3 - Polyurethane spring mattress (1) according to the first claim, characterised in that said springs (5) can be made up of different numbers of spirals (5.1) for different springs within a single mattress and are distributed in relation to the area of the mattress and the relative distribution of a person's weight, with the objective of varying the resistance to compression of said springs and therefore of the mattress.

4 - Polyurethane spring mattress (1) according to the first claim, characterised in that the springs (5) of said mattress have the shape of the trunk of a pyramid (9) and are provided with spirals (5.1) and are shaped by cutting a parallelepiped rectangular block of polyurethane foam by means of a specific programmable machine in two steps: a first step for shaping by means of a cutting blade manoeuvred by said machine, which covers the entire length or width of the polyurethane block, two first opposite faces of each spring (5) and partially, two platforms (6) into which all of the springs (5) of each mattress (1) are integrated, and a second step for shaping by means of the same cutting blade manoeuvred by said machine, which covers the entire length or width of the polyurethane block, a second pair of opposite faces adjacent to the first two faces and completely the two platforms (6) in which all of the springs (5) of each mattress are integrated, after turning said block 90° around a vertical axis, producing less than 1% of the material of the block as waste product since two essentially equal and complementary pieces are obtained.

5 - Polyurethane spring mattress (1) according to the first claim, characterised in that each spring (5) acts as a perfectly elastic part that, after being deformed under

the action of a force, recovers its original shape and position in a natural way once the action of said force has ceased.

- 6 - Polyurethane spring mattress (1) according to the first claim, characterised  
5 in that it is provided with a visco-elastic layer of polyurethane (3) and knit padding (2).



**ABSTRACT**

5           The mattress (1) is made of a block of flexible polyurethane foam (4) with a density of 40 Kg/m<sup>3</sup> or of any other density, said block being firstly cut with a cut programmable automatic machine, by the main side and then turned at a 90° degree angle by its small side. A certain amount of springs (5) is thereby formed depending on each type of mattress (1).

10

          The amount of spirals (5.1) of every spring (5) depends on the position of each spring in the mattress (1) with the purpose of varying the flexibility thereof so that the mattress (1) can perfectly adapt to the contour to of every user or so that the flexibility can remain constant throughout the entire mattress. Multiple variations can be realized while the height of the mattress remains the same (less spirals having the same spiral thickness and more base and uncut, etc.; the width of a spiral can be changed, as well as the number of spirals, the inclination of the axis of the spirals, the total height of an area-budge or cavity, etc. The upper surface of the product is covered with a viscous elastic layer (3) of polyurethane with a 50 Kg/m<sup>3</sup> density, 4 cm thickness and threaded padding (2)

20

**Form PTO 2038**